

Mayne Island - SGI



VE7GIM

HF Voice	Description	Equipment	Position Label	Status	CRD	Prov
3735.0	EMBC - primary	Kenwood TS-480SAT	HF Voice 1	When Activated	X	X
3745.0	EMBC - secondary	Kenwood TS-480SAT	HF Voice 1	When Required		
3729.0	BCPS	Kenwood TS-480SAT	HF Voice 1	When Required		
7060.0	EMBC - primary	Kenwood TS-480SAT	HF Voice 1	When Required		
7070.0	EMBC - secondary	Kenwood TS-480SAT	HF Voice 1	When Required		

HF Data - Center (USB)	Description	Equipment	Position Label	Status	CRD	Prov
3591.5	RMS - secondary	Kenwood TS-480SAT	HF 1	When Required		
3615.0	RMS - Primary	Kenwood TS-480SAT	HF 1	When Activated	X	X
3691.5	RMS - secondary	Kenwood TS-480SAT	HF 1	When Required		
7091.0	RMS - secondary	Kenwood TS-480SAT	HF 1	When Required		

VHF Voice	Description	Equipment	Position Label	Status	CRD	Prov
146.430	SGI	Kenwood TM-V71A	VHF Voice	When Activated	X	
146.460	Salt Spring	Kenwood TM-V71A	VHF Voice	When Required		
146.490	PEMO	Kenwood TM-V71A	VHF Voice	When Required		
146.580	NGO's	Kenwood TM-V71A	VHF Voice	When Required		
145.430 - 100.0 Hz tone	CRERCC - primary	Kenwood TM-V71A	VHF Voice	When Activated	X	X
145.430 100.0 Hz tone	CRERCC - secondary	Kenwood TM-V71A	VHF Voice	When Required		
147.570	CRERCC - backup	Kenwood TM-V71A	VHF Voice	When Required		
147.320 +	VE7RSI (Salt Spring)	Kenwood TM-V71A	VHF Voice	When Required		
146.660 - 100.0 Hz tone	WARA (Saltspring)	Kenwood TM-V71A	VHF Voice	When Required		
145.290 - 167.9 Hz tone	VE7SER (Mt Doug)	Kenwood TM-V71A	VHF Voice	When Required		
147.360 + 110.9 Hz tone IRLP 1980 Echolink 496228	VE7RSC (Surrey)	Kenwood TM-V71A	VHF Voice	When Required		

UHF Voice	Description	Equipment	Position Label	Status	CRD	Prov
446.050	SGI	Kenwood TM-V71A	UHF Voice	When Activated	X	
446.350	Saltspring	Kenwood TM-V71A	UHF Voice	When Required		
446.150	PEMO	Kenwood TM-V71A	UHF Voice	When Required		
444.925 + 100.0 Hz tone	CRERCC - primary	Kenwood TM-V71A	UHF Voice	When Activated	X	X
444.925 100.0 Hz tone	CRERCC - secondary	Kenwood TM-V71A	UHF Voice	When Required		
446.375	CRERCC - backup	Kenwood TM-V71A	UHF Voice	When Required		
443.775 + 110.9 Hz tone IRLP 1463	VE7RSC (Surrey)	Kenwood TM-V71A	UHF Voice	When Required		
444.875 + 107.2 Hz tone	VE7USA	Kenwood TM-V71A	UHF Voice	When Required		

VHF Data	Description	Equipment	Position Label	Status	CRD	Prov
144.970	Packet - primary	IC-2200H	VHF Data	24/7/365	X	X
145.690	Packet - secondary	IC-2200H	VHF Data	When Required		

UHF Data	Description	Equipment	Position Label	Status	CRD	Prov
440.125	Packet - primary	Kenwood TM-241A	UHF Data	24/7/365		X

Yellow highlighted area info still needed, except CRD column